



Conductivity measuring cell $c = 1.6 \text{ cm}^{-1}$ with Pt1000 (fixed cable, 0.65 m)

6.00929.140

3-conductor conductivity measuring cell with cell constant $c = 1.6 \text{ cm}^{-1}$ (guide value), with integrated Pt1000 temperature sensor and with fixed cable (0.65 m) for connecting to the OMNIS Measuring Module Conductivity.

This sensor is suitable for measurements of high conductivities (0.1 to 1,000 mS/cm), e.g., in:

- Sea water
- Flush water
- Physiological solutions

Below, the accessories are grouped into Scope of delivery and Optional accessories.

Please keep this printout at hand for ordering replacement material.

These lists may be subject to change.

Scope of delivery 6.00929.140

Qt.	Order no.	Description
-----	-----------	-------------

20 Stk 6.1236.050 Sleeve with SGJ 14/12 mm
Sleeve with SGJ 14/12 mm, polyethylene.



20 Stk 6.2008.040 Storage vessel

Together with 6.2008.050 storage vessel holder. it provides a support for the electrode on 807 Dosing Units.



Optional accessories

Order no.	Description
6.2301.060	KCl ion standard 250 mL KCl ion standard ($c(\text{ion}) = 0.1000 \pm 0.0005 \text{ mol/L}$), can also be used as standard solution for conductometry 12.87 mS/cm (25°C). 
6.02101.020	Measuring module conductivity Measurement channel for one OMNIS Titrator or Titration Module for the connection of conductivity measuring cells. 