



Metrosep A Supp 10 - 250/2.0

6.1020.230

The Metrosep A Supp 10 - 250/2.0 separation column is based on a high-capacity polystyrene-divinylbenzene copolymer with a particle size of only 4.6 μm . This proven column concept optimized by Metrohm is characterized by its robust construction, great selectivity and outstanding separating efficiencies. The 2 mm Metrosep A Supp 10 separation columns are packed with the same material as the corresponding 4 mm separation columns. Temperature, flow and eluent composition can be used to modify the properties of the column to accommodate the current application directly.

The Metrosep A Supp 10 - 250/2.0, as a microbore column, has a very high capacity. It is suitable for samples with high ionic strength, for complex separation tasks and for analyses in which great differences in concentration between the individual components are present. Thanks to its low flow, this microbore separation column is ideally suitable for IC-MS applications.

Below, the accessories are grouped into Scope of delivery and Optional accessories.

Please keep this printout at hand for ordering replacement material.

These lists may be subject to change.

Scope of delivery 6.1020.230

Qt.	Order no.	Description
-----	-----------	-------------

2 PCS

6.2744.060

Threaded stopper

For UNF 10/32. Stopper for IC, e.g. for the sealing of columns.



Optional accessories

Order no.	Description
6.1020.600	Metrosep A Supp 10 Guard/2.0 The Metrosep A Supp 10 Guard/2.0 column reliably protects the A Supp 10 analytical microbore separation columns against contamination. Thanks to the "On Column Guard System", the guard column is very easy to handle. The guard column screws easily and directly onto the analytical column without tools

