



894 Professional CVS manual

2.894.0210

894 Professional CVS manual is the entry-level instrument for high-end determinations of organic additives in electroplating baths with "Cyclic Voltammetric Stripping" (CVS), "Cyclic Pulse Voltammetric Stripping" (CPVS), and chronopotentiometry (CP). The proven Metrohm electrode methods combined with a high-performance potentiostat/galvanostat and the extremely flexible viva software open up new perspectives in CVS. The replaceable measuring head enables rapid changes between various applications with different electrodes. The potentiostat with a certified calibrator readjusts itself automatically before each measurement, thus guaranteeing maximum precision. The integrated temperature measurement input allows you to monitor the solution temperature during the measurement.

The viva software is required for control, data collection, and evaluation.

The 894 Professional CVS manual is supplied with extensive accessories and measuring head for rotating disk electrodes. Electrode set and viva license need to be ordered separately.

Phạm vi giao hàng 2.894.0210

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

1.894.0010

894 Professional CVS



1 PCS

6.1256.010

RDE measuring head for Professional VA/CVS
instruments

Measuring head for operation with rotating disk electrodes.



1 PCS

6.2151.000

Cable USB A – mini-DIN 8-pin

Controller cable



1 PCS

6.2703.000

Stand ring for titration vessels



1 PCS

6.2711.090

Drip pan for Professional VA/CVS instruments



2 PCS

6.2739.000

Wrench

For tightening connectors



1 PCS

6.2813.050

Dummy cell for Professional VA/CVS instruments



Phụ kiện tùy chọn

Order no.	Description
6.5339.000	CVS electrode equipment with 1 mm platinum electrode for Professional VA/CVS instruments Complete electrode set for the determination of organic additives in electroplating baths with CVS (Cyclic Voltammetric Stripping). Contains rotating platinum working electrode (electrode diameter: 1 mm), reference electrode, platinum auxiliary electrode, measuring vessels and electrolyte solutions. 
6.5339.010	CVS electrode equipment with 2 mm platinum electrode for Professional VA/CVS instruments Complete electrode set for the determination of organic additives in electroplating baths with CVS (Cyclic Voltammetric Stripping). Contains rotating platinum working electrode (electrode diameter: 2 mm), reference electrode, platinum auxiliary electrode, measuring vessels and electrolyte solutions. 
6.5339.020	CVS electrode equipment with 3 mm platinum electrode for Professional VA/CVS instruments Complete electrode set for the determination of organic additives in electroplating baths with CVS (Cyclic Voltammetric Stripping). Contains rotating platinum working electrode (electrode diameter: 3 mm), reference electrode, platinum auxiliary electrode, measuring vessels and electrolyte solutions. 
6.5339.500	Equipment with 2x 807 Dosing Units for VA and CVS measurements Accessory set for 2 auxiliary solutions for expanding VA or CVS systems. Contains 2x 807 Dosing Units 2 mL, 2x 100 mL clear glass bottles, bottle holder for 2 bottles, and connector material. Without Dosinos. 

6.1110.120

Pt1000 temperature sensor for CVS (installation length 9 cm)

Pt1000 temperature sensor (class B) for Professional CVS Instruments.



6.2104.140

Electrode cable / 1 m / 2 x 2 mm

For connecting temperature sensors with Metrohm plug-in head G with 780, 781, 826, 827 pH/Ion meters and all Titrandos



6.1454.130

Form seal made of FPM for 61414xxx

for KF and VA instruments



6.5339.060

CVS electrode equipment with 2 mm platinum electrode for Professional VA/CVS instruments for intensive use

Complete electrode set for the determination of organic additives in electroplating baths with CVS (Cyclic Voltammetric Stripping). Contains rotating platinum working electrode (electrode diameter: 2 mm), driving axle with mercury contact, maintenance-free gel reference electrode, platinum auxiliary electrode, measuring vessels and KCl electrolyte solution.



Drive with write/read hardware for intelligent dosing units. With permanently attached cable (length 0.65 m).



6.5339.110

CVS electrode equipment with 2 mm platinum electrode, gel reference electrode and steel auxiliary electrode for Professional VA/CVS instruments

Complete electrode set for the determination of organic additives in electroplating baths with CVS (Cyclic Voltammetric Stripping). Contains rotating platinum working electrode (electrode diameter: 2 mm), driving axle with mercury contact, maintenance-free gel reference electrode, steel auxiliary electrode, measuring vessels and KCl electrolyte solution.



6.5339.520

Equipment with two 807 Dosing Units (2 + 50 mL) for CVS measurements

Accessory set for two auxiliary solutions for expanding CVS systems. Includes one 2 mL and one 50 mL 807 Dosing Unit each, clear glass bottles 100 mL and 2 L, bottle holders for 2 bottles, one 2-way microtip, and connector material. Without Dosinos.



6.5339.600

Equipment with the 807 Dosing Unit for automatic sample transfer for VA and CVS measurements

Accessory set for expanding VA or CVS systems for automatic sample transfer with the Dosino. Includes one 5 mL 807 Dosing Unit, one Dosino holder and connector material. Without Dosino.



Computer program for control and data management of Professional VA /CVS instruments. The software permits checks, data acquisition, evaluation, and monitoring, as well as generation of reports.

Graphic user interface for routine operations, extensive database programs with reevaluation, graphic method editor with numerous templates, system configuration, very flexible user management, extensive data export functions, individually configurable report generator.

Includes the "Differential Pulse" (DP), "Square Wave" (SQW), "Linear Sweep Voltammetry" (LSV), "Cyclic Voltammetry" (CV), "Cyclic Voltammetric Stripping" (CVS), "Cyclic Pulse Voltammetric Stripping" (CPVS), and Chronopotentiometry (CP) measuring modes. The following calibration techniques are supported: Standard addition, external calibration, DT (Dilution Titration), LAT (Linear Approximation Technique), MLAT (Modified Linear Approximation Technique), RC (Response Curve).

Dialog languages: German, English, Chinese, Japanese.

The following instruments are supported: 884 Professional VA, 894 Professional CVS

1 license for a maximum of 4 Professional VA/CVS instruments on a single computer. Contains USB flash drive and installation documentation.



Client/server-compatible computer program for control and data management of Professional VA/CVS instruments. The software permits checks, data acquisition, evaluation, and monitoring, as well as report generation.



Graphic user interface for routine operations, extensive database programs with reevaluation, graphic method editor with numerous templates, system configuration, very flexible user management, extensive data export functions, individually configurable report generator.

Includes the "Differential Pulse" (DP), "Square Wave" (SQW), "Linear Sweep Voltammetry" (LSV), "Cyclic Voltammetry" (CV), "Cyclic Voltammetric Stripping" (CVS), "Cyclic Pulse Voltammetric Stripping" (CPVS), and Chronopotentiometry (CP) measuring modes. The following calibration techniques are supported: Standard addition, external calibration, DT (Dilution Titration), LAT (Linear Approximation Technique), MLAT (Modified Linear Approximation Technique), RC (Response Curve).

Dialog languages: German, English, Chinese, Japanese.

The following instruments are supported: 884 Professional VA, 894 Professional CVS

Client/server version with 3 licenses for 3 computers with a max. of 4 Professional VA/CVS instruments per computer. Contains USB flash drive and installation documentation.
