



916 Salt Ti-Touch

2.916.2010

"Reduce to the max" – this is the 916 Ti-Touch concept. The new compact titrator from Metrohm offers the maximum in the class of stand-alone systems for routine analysis.

The 916 Ti-Touch now also fulfills FDA Regulation 21 CFR, Part 11. This means you are always on the safe side when it comes to audits.

The 916 Salt Ti-Touch offers you the complete package for the analysis of chloride in a wide variety of samples. In addition to the determination methods described in detail, you also receive the complete accessories for your titrations. Included in the package are titrator with rod stirrer, 800 Dosino, 20 mL dosing unit and an iAg-Titrode for precipitation titration with silver nitrate.

Phạm vi giao hàng 2.916.2010

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

1.800.0040

800 Dosino (cable length 0.65 m)

Drive with write/read hardware for intelligent dosing units. With permanently attached cable (length 0.65 m).



1 PCS

1.802.0020

802 Stirrer

Rod stirrer for sample changer and Sample Processor.

With 6.1909.020 Propeller stirrer 104 mm and fixed cable.



1 PCS

1.854.0010

854 iConnect

854 iConnect - electrode cable and measuring amplifier for intelligent electrodes «iTrodes».



Intelligent, combined silver ring electrode with a pH glass membrane as reference electrode and integrated memory chip for storing sensor data. This maintenance-free electrode is suitable for precipitation titrations when the pH value remains constant (titrant silver nitrate), for example of:

- Chloride, Bromide, Iodide
- Sulfides
- Hydrogen sulfide
- Mercaptans
- Cyanides

This electrode is stored in distilled water.

Depending on the application, we recommend using an Ag Titrode with Ag_2S coating, which can be ordered accordingly.

iTodes can be used on Titrando, Ti-Touch or 913/914 meters.



For pistons for 807 Dosing Units or cylinder units OMNIS.



For Exchange Units. Bottle for auxiliary solutions.



1 PCS

6.1909.010

Stirring propeller / 87 mm

Propeller stirrer, length from lower edge of SGJ: 96 mm. For use with beakers with 722, 802 Rod Stirrer



1 PCS

6.2013.010

Clamping ring

For support rods with a diameter of 10 mm.



1 PCS

6.2016.050

Support rod / 300 mm



2 PCS

6.2043.005

Holding clip for bottles

Holding spring for reagent bottles in exchange units.



1 PCS

6.2164.010

Power supply unit 100 - 240 V/24 V DC

Power supply unit for 915 KF Ti-Touch, 916 Ti-Touch, 917 Coulometer and all Eco Titrators / Eco Dosimat.



1 PCS

6.2621.030

Hexagon key 4 mm



1 PCS

6.2709.070

Guiding sleeve

For fixation of buret and dosing tips in titration heads and electrode holders



1 PCS

6.3032.220

807 Dosing Unit 20 mL

807 Dosing Unit with integrated data chip with 20 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



1 PCS

6.6066.000

USB flash drive for Ti-Touch

USB flash drive for 915 KF Ti-Touch and 916 Ti-Touch.



1 PCS

6.02005.000

OMNIS electrode holder

Electrode holder for one OMNIS titration system.



1 PCS

6.2723.300

Protective cover for 900 Touch Control

Protective cover for 900 Touch Control



Phụ kiện tùy chọn

Order no.	Description	
2.800.0010	800 Dosino	
2.805.0010	805 Dosimat	
6.3026.110	Exchange Unit 1 mL	
6.3026.150	Exchange Unit 5 mL	

6.3026.210

Exchange Unit 10 mL

Exchange unit with integrated data chip with 10 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



6.3026.220

Exchange Unit 20 mL

Exchange unit with integrated data chip with 20 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



6.3026.250

Exchange unit 50 mL

Exchange unit with integrated data chip with 50 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, antidiffusion tip and standard amber glass reagent bottle.



6.3032.120

807 Dosing Unit 2 mL

807 Dosing Unit with integrated data chip with 2 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.3032.150

807 Dosing Unit 5 mL

807 Dosing Unit with integrated data chip with 5 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.3032.210

807 Dosing Unit 10 mL

807 Dosing Unit with integrated data chip with 10 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.3032.250

807 Dosing Unit 50 mL

807 Dosing Unit with integrated data chip with 50 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



6.2723.300

Protective cover for 900 Touch Control

Protective cover for 900 Touch Control



Sample Processor for the automated analysis of routine samples using 916 Ti-Touch or 915 KF Ti-Touch.

Sample Processor with one workstation and one built-in membrane pump for the automatic processing of potentiometric as well as Karl Fischer titrations, in series with small to medium quantities. In addition to the built-in pump, an additional one (membrane or peristaltic) and up to three dosing devices for Liquid Handling tasks can be connected.

Because of the multitude of application variants, rack, stirrer, titration head, Swing Head and sample vessels must be tailored to the application and ordered separately.



Titration stand and controller for 802 Rod Stirrer. The 804 Ti Stand together with the optional 802 Rod Stirrer provides an alternative to the magnetic stirrer. Ti Stand with base plate, support rod and electrode holder.



Compact printer with USB interface for

- 900 Touch Control
- 915 KF Ti-Touch
- 916 Ti-Touch
- 917 Coulometer
- 877 / 848 Titrino plus
- 865 / 876 Dosimat plus
- 91X Meter (cable 6.2151.140)
- Eco Dosimat / Titrator
- 862 Compact Titrosampler
- 870 KF Titrino plus
- 899 Coulometer



Paper width 60 mm (40 characters). Including 6.2151.120 USB cable.

Handle for manual dosing and manual titration with the 916 Ti-Touch and the 900 Touch Control. Requires 6.2148.010 Remote Box MSB.



Compact impact printer with USB and RS232 interface for

- 900 Touch Control (+)
- 915 KF Ti-Touch (+)
- 916 Ti-Touch (+)
- 917 Coulometer (+)
- 91X Meter (+)
- Eco Dosimat/Titrator (+)
- 877/848 Titrino plus (additional 6.2151.100 required)
- 865/876 Dosimat plus (additional 6.2151.100 required)
- 862 Compact Titrosampler (additional 6.2151.100 required)
- 870 KF Titrino plus (additional 6.2151.100 required)
- 899 Coulometer (additional 6.2151.100 required)



(+) Cable included in scope of delivery