



Combined iAg-ring electrode

6.00450.300

Intelligent, combined silver ring electrode with integrated memory chip for storing sensor data. This electrode is suitable for precipitation titrations when the pH value varies (titrant silver nitrate) of, e.g.:

- chloride, bromide, iodide
- sulfides
- hydrogen sulfide
- mercaptans
- cyanides

The fixed ground-joint diaphragm is insensitive to contamination and the permanently fused-in silver ring is resistant to more highly concentrated acids and saline solutions.

$c(\text{KNO}_3) = 1 \text{ mol/L}$ is used as reference electrolyte and storage solution.

Phạm vi giao hàng 6.00450.300

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

6.1236.050

Sleeve with SGJ 14/12 mm

Sleeve with SGJ 14/12 mm, polyethylene.



1 PCS

6.2008.040

Storage vessel

Together with 6.2008.050 storage vessel holder. it provides a support for the electrode on 807 Dosing Units.



Phụ kiện tùy chọn

Order no.	Description	
2.854.0010	854 iConnect The 854 iConnect – Electrode cable and measuring amplifier for intelligent "iTrodes" electrodes (cable length 150 cm).	
6.2310.010	Electrolyte KNO3-1mol/L 250 mL Electrolyte solution KNO ₃ 1 M (reference electrolyte for combined silver electrodes)	