



Separate Pt Rod Electrode

6.0331.000

This metal electrode has to be used in combination with a reference electrode ($c(\text{KCl}) = 3 \text{ mol/L}$ as reference electrolyte) and is well suited:

- for redox titrations
- as an auxiliary electrode for differential potentiometry

The robust shaft made of polypropylene and the metal rod can be replaced separately.

Phạm vi giao hàng 6.0331.000

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

6.2106.020

Strand / 1 m / 2 x B

Electrode cable with 2 x plug B (4 mm) for connecting electrodes
with plug-in head B



Phụ kiện tùy chọn

Order no.	Description	
6.1241.030	Electrode shaft Electrode shaft for separate metal pin electrodes	
6.1248.000	Platinum Electrode Rod Platinum Electrode Rod for separate metal pin electrode	
6.0729.100	Ag/AgCl reference electrode (length 12.5 cm) Silver/silver chloride reference electrode with Double-Junction System and separate shielding, installation length 10 cm. This reference electrode is well-suited for: • Nonaqueous samples • Differential potentiometry The standard ground-joint 14/15 enables easy assembly, and the flexible ground-joint diaphragm, which is insensitive to contamination, can be replaced at any time. The reference electrolyte and the bridge electrolyte can be selected freely according to use, and are easy to replace. The sensor is supplied without electrolyte filling.	

6.2308.020

Electrolyte 3 mol/L KCl (250 mL)

Electrolyte solution $c(\text{KCl}) = 3 \text{ mol/L}$, (for Ag/AgCl reference systems)

