



Separate Ag-rod electrode

6.0331.010

This metal electrode has to be used in combination with a reference electrode ($c(\text{KNO}_3) = 1 \text{ mol/L}$ as reference electrolyte) and is well suited for precipitation titrations (titrant silver nitrate). The robust shaft made of polypropylene and the metal rod can be replaced separately.

Phạm vi giao hàng 6.0331.010

Qt.	Order no.	Description
1 PCS	6.2106.020	Strand / 1 m / 2 x B
		Electrode cable with 2 x plug B (4 mm) for connecting electrodes with plug-in head B



Phụ kiện tùy chọn

Order no.	Description	
6.1241.030	Electrode shaft Electrode shaft for separate metal pin electrodes	
6.1248.010	Silver Electrode Rod Silver Electrode Rod for separate metal pin electrode	
6.0729.100	Ag/AgCl reference electrode (length 12.5 cm) Silver/silver chloride reference electrode with Double-Junction System and separate shielding, installation length 10 cm. This reference electrode is well-suited for: • Nonaqueous samples • Differential potentiometry The standard ground-joint 14/15 enables easy assembly, and the flexible ground-joint diaphragm, which is insensitive to contamination, can be replaced at any time. The reference electrolyte and the bridge electrolyte can be selected freely according to use, and are easy to replace. The sensor is supplied without electrolyte filling.	