



Ag/AgCl reference electrode (length 12.5 cm)

6.0729.100

Silver/silver chloride reference electrode with Double-Junction System and separate shielding, installation length 10 cm.

This reference electrode is well-suited for:

- Nonaqueous samples
- Differential potentiometry

The standard ground-joint 14/15 enables easy assembly, and the flexible ground-joint diaphragm, which is insensitive to contamination, can be replaced at any time. The reference electrolyte and the bridge electrolyte can be selected freely according to use, and are easy to replace. The sensor is supplied without electrolyte filling.

Phạm vi giao hàng 6.0729.100

Qt.	Order no.	Description
-----	-----------	-------------

Together with 6.2008.050 storage vessel holder, it provides a support for the electrode on 807 Dosing Units.



Phụ kiện tùy chọn

Order no.	Description	
6.1243.030	Diaphragm for reference electrode Spare ground-joint diaphragm for 6.0726.1XX and 6.0729.1XX reference electrodes	
6.2308.020	Electrolyte 3 mol/L KCl (250 mL) Electrolyte solution $c(\text{KCl}) = 3 \text{ mol/L}$, (for Ag/AgCl reference systems)	
6.2310.010	Electrolyte KNO_3 -1 mol/L 250 mL Electrolyte solution KNO_3 1 M (reference electrolyte for combined silver electrodes)	
6.2320.000	TEABr 0.4 mol/L in ethylene glycol (250 mL) Electrolyte solution TEABr (tetraethylammonium bromide in ethylene glycol), $c(\text{TEABr}) = 0.4 \text{ mol/L}$	

6.2104.020

Electrode cable / 1 m / F

For connecting electrodes with Metrohm plug-in head G to Metrohm instruments (socket F).



6.2129.010

Differential amplifier, plug F

Differential amplifier with plug F, for Titrados (power supply unit must be ordered separately: 6.2117.000 power unit EU 230 V / 9 V AC)

Also available as a complete set: 6.5104.030 differential amplifier / plug F / 230 V EU

