



5-ring conductivity measuring cell $c = 1.0 \text{ cm}^{-1}$ with Pt1000 (fixed cable)

6.0915.130

5-ring conductivity measuring cell with cell constant $c = 1.0 \text{ cm}^{-1}$ (guide value), with integrated Pt1000 temperature sensor and with fixed cable (1.2 m) for connecting to an 856 Conductivity Module in combination with a sample changer.

This sensor is suitable for automated measurements of medium conductivities ($5 \mu\text{S/cm}$ to 100 mS/cm), e.g., in:

- drinking water
- surface water
- wastewater

Phạm vi giao hàng 6.0915.130

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

6.1236.050

Sleeve with SGJ 14/12 mm

Sleeve with SGJ 14/12 mm, polyethylene.



1 PCS

6.2008.040

Storage vessel

Together with 6.2008.050 storage vessel holder. it provides a support for the electrode on 807 Dosing Units.



Phụ kiện tùy chọn

Order no.	Description
6.2301.060	KCl ion standard 250 mL KCl ion standard ($c(\text{ion}) = 0.1000 \pm 0.0005 \text{ mol/L}$), can also be used as standard solution for conductometry 12.87 mS/cm (25°C). 
6.2324.110	Conductivity standard $100 \mu\text{S/cm}$, 5 x 30 mL Conductivity standard for calibration of conductivity measuring cells with cell constant = $0.1/\text{cm}$. 
6.2324.010	Conductivity standard $100 \mu\text{S/cm}$ 250 mL Conductivity standard for calibration of conductivity measuring cells with cell constant = $0.1/\text{cm}$. 